

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.09.2018

Version 2

Revision: 26.09.2018

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- 1.1 Product identifier
- Trade name: Terra Primer 5
- Application of the substance / the mixture Priming
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Decorative
Products GmbH-Kurt Fischer Str.32
D-22926 Ahrensburg Germany
Tel.: 0049/(0) 4102 4694-00
Fax.: 0049/(0)4102 4694-11
- Further information obtainable from: Tel.: 0049- (0)
4102 4694-00 E-Mail: info@decorative-products.de
- 1.4 Emergency telephone number: Tel.: 0049- (0) 89- 192 40
(emergency telephone no.) Tel.: 0049/621/60-43333 (EASF Plant fire
brigade)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the CLP regulation.
- Hazard pictograms GHS02, GHS05, GHS07, GHS08, GHS09

(Contd. on page 1)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.09.2018

Version 2

Revision: 26.09.2018

Trade name: Terra Primer 5

(Contd. of page 1)

- Signal word Danger
- Hazard-determining components of labelling:
Isoalkane C7-C9
tetra-n-butoxytitanium
- Hazard statements
H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.
H304 May be fatal if swallowed and enters airways.
H411 Toxic to aquatic life with long lasting effects.
- Precautionary statements
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves / eye protection / face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P304+P312 IF INHALED: Call a POISON CENTER/doctor if you feel unwell.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Chemical characterisation: Mixtures
 - Description: Solvent mixture with additives.
 - Dangerous components:
- | | | |
|---------------------------|--|----------|
| CAS: 90622-56-3 | Isoalkane C7-C9 | 80 - 95% |
| EINECS: 292-458-5 | Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336 | |
| Reg.nr.: 01-2119471305-42 | | |
| CAS: 5593-70-4 | tetra-n-butoxytitanium | < 5% |
| EINECS: 227-006-8 | Flam. Liq. 3, H226; Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335-H336 | |
| Reg.nr.: 01-2119967423-33 | | |
| CAS: 78-10-4 | tetraethyl silicate | < 2% |
| EINECS: 201-083-8 | Flam. Liq. 3, H226; Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335 | |
| Reg.nr.: 01-2119496195-28 | | |
- Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.09.2018

Version 2

Revision: 26.09.2018

Trade name: Terra Primer 5

(Contd. of page 2)

- After inhalation
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
- After skin contact
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- After eye contact Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing Do not induce vomiting; call for medical help immediately. Show container or label.
- 4.2 Most important symptoms and effects, both acute and delayed
Headache
Dizziness
Dizziness
Nausea
- 4.3 Indication of any immediate medical attention and special treatment needed
If swallowed or in case of vomiting, danger of entering the lungs

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
Suitable extinguishing agents CO₂, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents Water with full jet.
- 5.2 Special hazards arising from the substance or mixture
Formation of toxic gases is possible during heating or in case of fire.
- 5.3 Advice for firefighters
Protective equipment: Do not inhale explosion gases or combustion gases.
- Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
Ensure adequate ventilation
Keep away from ignition sources
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.
Dispose contaminated material as waste according to item 13.
- 6.4 Reference to other sections See Section 8 for information on personal protection equipment.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling
Ensure good ventilation/exhaustion at the workplace.
see item 8: Personal protective equipment
- Information about fire - and explosion protection:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Traces of flammable substances may collect in the steam chamber of enclosed systems. Keep clear of ignition sources.
Highly volatile, flammable constituents are released during processing.
Flammable gas-air mixtures may form in empty receptacles.

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.09.2018

Version 2

Revision: 26.09.2018

Trade name: Terra Primer 5

(Contd. of page 3)

- 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- Requirements to be met by storerooms and receptacles:
Provide solvent resistant, sealed floor.
Prevent any seepage into the ground.
- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
Store receptacle in a well ventilated area.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:
- Additional information: The Lists valid during the making were used as basis.
- 8.2 Exposure controls
- Personal protective equipment
- General protective and hygienic measures
The usual precautionary measures are to be adhered to when handling chemicals.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- Respiratory protection:
Use suitable respiratory protective device when high concentrations are present.
- Protection of hands: Protective gloves.
- Material of gloves
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
Fluorocarbon rubber (Viton)
Recommended thickness of the material: > 0.4 mm
- Penetration time of glove material Breakthrough time: > 60 min
- Eye protection: Tightly sealed goggles.
- Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- General Information
- Appearance:

Form:	Fluid
Colour:	Colourless
Odour:	Characteristic
- Odour threshold: Not determined.
- pH-value: Not determined.
- Change in condition

Melting point/freezing point:	undetermined
Initial boiling point and boiling range:	116 °C

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.09.2018

Version 2

Revision: 26.09.2018

Trade name: Terra Primer 5

(Contd. of page 4)

- Flash point: 6 °C
- Ignition temperature: >200 °C
- Auto-ignition temperature: Product is not selfigniting.
- Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- Explosion limits:
 - Lower: 0.7 Vol %
 - Upper: 6 Vol %
- Oxidising properties: Not determined.
- Vapour pressure at 20 °C: 19 hPa
- Density: see technical datasheet
- Vapour density: Not applicable.
- Evaporation rate: Not determined.
- Solubility in / Miscibility with Water: Not determined.
- Partition coefficient: n-octanol/water: Not determined.
- Viscosity: Not determined.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
No decomposition if used according to specifications.
Avoid strong heating.
- 10.3 Possibility of hazardous reactions
Danger of receptacles bursting because of high vapour pressure when heated
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised
- 10.5 Incompatible materials: Strong oxidizing agents, alkalis, amines, strong acids
- 10.6 Hazardous decomposition products: see item 5.2

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:
90622-56-3 Isoalkane C7-C9
- Oral LD50 >5,000 mg/kg (rat)
- Dermal LD50 >2,000 mg/kg (rat)
- Inhalative IC50/4 h 2l mg/l (rat) 5593-70-4 tetra-n-butoxytitanium
- Oral LD50 3,122 mg/kg (rat)
- 78-10-4 tetraethyl silicate
- Oral LD50 6,270 mg/kg (rat)
- Dermal LD50 5,860 mg/kg (rab)
- Inhalative IC50/4 h 10 mg/l (rat)

(Contd. on page 5)

e GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.09.2018

Version 2

Revision: 26.09.2018

Trade name: Terra Primer 5

(Contd. of page 5)

- Primary irritant effect:
- Skin corrosion/irritation
Causes skin irritation.
- Serious eye damage/irritation
Causes serious eye damage.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure
May cause drowsiness or dizziness.
- SIOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard
May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- Ecotoxicological effects:
- Remark: Toxic for fish
- Additional ecological information:
- General notes:
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water. Do not allow product to reach ground water, water course or sewage system.
Also poisonous for fish and plankton in water bodies.
The material is harmful to the environment.
Toxic for aquatic organisms
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation
Liquid residues must be specially treated adhering to official regulations. Observe local by-laws.
- Uncleaned packaging:
- Recommendation:
Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning. Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

- 14.1 UN-Number
- ADR, IMDG, IATA UN1993
- 14.2 UN proper shipping name
- ADR 1993 FLAMMABLE LIQUID, N.O.S. (Isocalkane C7 - C10)
- IMDG FLAMMABLE LIQUID, N.O.S. (Isocalkane C7-C9),
MARINE POLLUTANT

(Contd. on page 6)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.09.2018

Version 2

Revision: 26.09.2018

Trade name: Terra Primer 5

(Contd. of page 6)

IATA	FLAMMABLE LIQUID, N.O.S. (Isoalkane C7-C9)
14.3 Transport hazard class(es)	
ADR	
Class	3 (F1) Flammable liquids.
Label	3
• IMDG	
• Class	3 Flammable liquids.
• Label	3
IATA	
Class 3 Flammable liquids.	
Label	3
14.4 Packing group	
ADR, IMDG, IATA	II
14.5 Environmental hazards:	
Marine pollutant:	Yes
	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	3
EMS Number:	F-E, S-E
Stowage Category	B
14.7 Transport in bulk according to Annex II of	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
• ADR	
• Limited quantities (LQ)	1L
• Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
• UN "Model Regulation":	UN1993, FLAMMABLE LIQUID N.O.S. (Isoalkane C7-C10), ENVIRONMENTALLY HAZARDOUS, 33, II

GB

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.09.2018

Version 2

Revision: 26.09.2018

Trade name: Terra Primer 5

(Contd. of page 7)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- National regulations
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- Details of international registration status:
Listed on or in accordance with the following inventories:
REACH - Europe listed
AICS - Australia listed
DSL- Canada listed
IECSC - China listed
ENCS - Japan listed
NZIoC - New Zealand listed PICCS -
Philippines listed ECL - Korea listed
TSCA - USA listed
TCSI - Taiwan listed
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation. H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
- Department issuing SDS: Tel.: 0049- (0)4102 4694-00
- Contact: Tel.: 0049- (0)4102 4694-00
- Abbreviations and acronyms:
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable Liquids - Category 2

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 26.09.2018

Version 2

Revision: 26.09.2018

Trade name: Terra Primer 5

(Contd. of page 8)

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

- * Data compared to the previous version altered.